

Grade 30 Proof Coil Chain Specifications

A general purpose chain for all ordinary applications not requiring high strength characteristics. Frequently used for light duty tow chains, tie down chains and logging chains. Identified with "L3" or similar grade marking. Self-colored, Electro Zinc plated and hot dip galvanized in stock.

Sizes 1/4, 5/16 and 3/8 are stocked in "Long Link" design which provides the same working load limits in a lighter weight chain. We reserve the right to substitute regular link. Other chain stocked in "Regular Link" only.

Not for overhead lifting.

Manufactured to specifications developed by the National Association of Chain Manufacturers, Federal Specification RR-C-271, and ASTM/ANSI 413. Grade 30.



Made in the USA

The information on this page is to be used for comparison purposes only.

Trade Size (inch)	Pail Qty	Drum Qty	Working Load Limit (lbs)	Breaking Strength (lbs)	Link Mat'l Dia (inch)	Link Inside Length (inch)	Link Inside Width (inch)	Weight/ 100 ft (lbs)
1/8 reg link	500'	2000'	400	1600	.160	.90	.27	21
3/16 reg link	250'	1600'	800	3200	.210	.95	.40	38
1/4 long link	141'	800'	1300	5200	.275	1.24	.46	63
1/4 reg link	141'	800'	1300	5200	.275	1.02	.50	.69
5/16 long link	92'	550'	1900	7600	.330	1.30	.49	91
5/16 reg link	92'	550'	1900	7600	.330	1.15	.49	1.00
3/8 long link	63'	400'	2650	10600	.397	1.45	.60	135
3/8 reg link	63'	400'	2650	10600	.397	1.30	.60	145
1/2 reg link	36'	200'	4500	18000	.520	1.56	.81	264
5/8 reg link	-	150'	6900	27600	.630	1.87	1.00	393
3/4 reg link	-	100'	10,600	42400	.787	2.13	1.13	628

*DO NOT USE FOR OVERHEAD LIFTING.
Do not exceed working load limit.*

1st Chain Supply



Your online source for all your chain and related supplies

Questions? Call us toll free
1-800-523-2367

(ask for "Chain Sales")

Monday thru Friday 8:00am to 4:30pm CST
24 Hour Fax Lines 1-219-696-6413