

Grade 43 High Test Chain Specifications

Designed for use in load binding, logging and other applications requiring higher strength to weight ratios than Grade 30 chain. Used extensively in the trucking industry for binder chains. Identified with "L4" or similar grade marking. Shot blast (self-colored) finish. Packaged in drums and pails.

Not for overhead lifting.

Manufactured to specifications developed by the National Association of Chain Manufacturers, Federal Specification RR-C-271, and ASTM/ANSI 413.



Made in the USA

Trade Size	Pail No.	Pail Qty	Drum No.	Drum Qty	Working Load Limit (lbs)	Breaking Strength (lbs)	Material Diameter	Inside Length	Inside Width	Weight/ 100 ft
1/4	38-315	135'	38-315D	800'	2600	7800	.275	1.02	.50	69
5/16	38-316	90'	38-316D	550'	3900	11700	.330	1.15	.49	100
3/8	38-317	63'	38-317D	400'	5400	16200	.397	1.30	.60	145
1/2	38-318	37'	38-318D	200'	9200	27600	.520	1.56	.81	265
<i>DO NOT USE FOR OVERHEAD LIFTING. Do not exceed working load limit.</i>						<i>Also available in 5/8</i>				

The information on this page is to be used for comparison purposes only.

1st Chain Supply

 Your online source for all your chain and related supplies

Questions? Call us toll free **1-800-523-2367**

(ask for "Chain Sales")

Monday thru Friday 8:00am to 4:30pm CST

24 Hour Fax Lines 1-219-696-6413