

## Grade 80 Alloy Chain Specifications

Rugged, versatile, high strength chain manufactured from special alloy steel. This chain is quenched and tempered and proof tested. Meets NACM, ASTM and OSHA specifications. Identified with "L8" or similar grade marking. *Gr 100 Alloy available on special order.* Certified lifting assemblies available on special order. Shot Blast (Self-colored) finish.

Packaged in drums, pails and cut to order.

**Approved for overhead lifting.**

Manufactured to specifications developed by the National Association of Chain Manufacturers, Federal Specification RR-C-271, and ASTM/ANSI 413.



Made in the USA

Trade Size	Pail No.	Pail Qty	Drum No.	Drum Qty	Working Load Limit (lbs)	Material Diameter (inches)	Inside Length (inches)	Inside Width (inches)	Weight/ 100 ft (lbs)
9/32	38-321	100'	38-321D	800'	3500	.279	.88	.41	72
5/16	38-328	70'	38-328D	550'	4500	.330	1.02	.48	106
3/8	38-322	45'	38-322D	400'	7100	.397	1.22	.57	150
1/2	38-323	25'	38-323D	200'	12000	.520	1.56	.75	261
5/8	38-329CL	ANY	38-329D	200'	18100	.630	1.93	.92	361
3/4	-	-	-	100'	28300	.787	2.36	1.22	605
7/8	-	-	-	100'	34200	.866	2.60	1.35	733
1"	-	-	-	100'	47700	1.023	3.07	1.59	1021
					<i>Do not exceed working load limit.</i>				

The information on this page is to be used for comparison purposes only.



Questions? Call us toll free **1-800-523-2367**

*(ask for "Chain Sales")*

Monday thru Friday 8:00am to 4:30pm CST

24 Hour Fax Lines 1-219-696-6413