



Sales Desk
1-800-523-2367

Option "3"
 (or 1-219-696-6411)
Fax: 219-696-6413
 email sales@firstchain.com

Stainless Steel Chain Specifications

The dimensions table below show our standard imported chain made to NACM specifications and US made chain that also conforms to NACM (1/8, 3/16, 5/8 and 3/4) dimensions. You will also find French made chain that conforms to Gr 40 (G4) and triple B (BBB) windlass chain (also called "ISO short link") specifications in 1/4, 5/16, 3/8 and 1/2" sizes.

Not for overhead lifting.

Trade Size	Country of Origin	Working Load Limit (lbs)	Material Diameter	Inside Length	Inside Width	Weight/ 100 ft (lbs)
1/8	China	375	0.156	0.94	0.25	17
5/32	USA	500	0.160	0.77	0.28	23
3/16	China	1,150	0.217	0.98	0.30	38
3/16	USA	930	0.200	0.92	0.30	32
1/4	China	1,860	0.275	1.24	0.38	61
1/4 G4*	FRANCE	2,000	0.280	0.84	0.40	78
1/4 BBB*	FRANCE	2,000	0.280	0.87	0.36	76
5/16	China	2,425	0.330	1.29	0.44	84
5/16 G4*	FRANCE	2,400	0.320	1.03	0.49	92
5/16 BBB*	FRANCE	2,400	0.320	0.95	0.41	94
3/8	China	3,800	0.394	1.38	0.55	140
3/8 G4*	FRANCE	3,550	0.390	1.22	0.61	150
3/8 BBB*	FRANCE	3,750	0.390	1.10	0.54	160
1/2	China	6,425	0.512	1.79	0.72	234
1/2 G4*	FRANCE	6,500	0.510	1.59	0.76	210
1/2 BBB*	FRANCE	6,500	0.510	1.38	0.74	274
5/8	China	9,725	0.630	2.20	0.79	358
5/8	USA	9,800	0.630	1.91	0.90	331
3/4	China	15,175	0.787	2.76	0.98	551
3/4	USA	15,000	0.750	2.75	1.17	500

***G4 and BBB stainless chain has the same dimensions as carbon steel anchor (windlass) chain of the same specification**

The information on this page is to be used for comparison purposes only. Please consult reliable engineering texts when danger to life or property is possible