


1st Chain Supply

12628 E Highway 86
 Neosho, MO 64850
 Sales 1-800-523-2367 Ext "3"
 Fax 417-451-5651

Grade 30 Proof Coil Chain Specifications

Proof coil chain is a general purpose chain for all ordinary applications not requiring high strength characteristics. Frequently used for light duty tow chains, tie down chains and logging chains. Identified with "L3" or similar grade marking. Self-colored, Electro Zinc plated and hot dip galvanized in stock. Available in drums and pails.



NOT FOR OVERHEAD LIFTING.

Trade Size	Working Load Limit (lbs) (4:1)	Material Diameter "T" (inches)	Inside Length "L" (inches)	Inside Width "W" (inches)	Weight per 100 ft (lbs)
1/8 reg link	400	0.160	0.900	0.270	21
3/16 reg link*	800	0.210	0.950	0.400	38
1/4 long link	1300	0.275	1.240	0.460	63
1/4 reg link*	1300	0.275	1.020	0.500	69
1/4 ISO SHORT link*	1300	0.279	1.000	0.510	73
5/16 long link	1900	0.330	1.300	0.490	91
5/16 reg link*	1900	0.330	1.150	0.490	100
5/16 ISO SHORT link*	1900	0.342	1.100	0.510	109
3/8 long link	2650	0.397	1.450	0.600	135
3/8 reg link*	2650	0.397	1.300	0.600	145
3/8 ISO SHORT link*	2650	0.404	1.230	0.620	155
1/2 reg link*	4500	0.520	1.560	0.810	264
1/2 ISO SHORT link*	4500	0.512	1.500	0.820	250
5/8 reg link*	6900	0.630	1.870	1.000	393
3/4 reg link*	10600	0.787	2.130	1.130	628
* starred items meet Fed Spec RR-C-271 Type 1, Class 4 (latest revision)			DO NOT USE FOR OVERHEAD LIFTING. <i>Do not exceed working load limit.</i>		

Manufactured to specifications developed by the
 National Association of Chain Manufacturers(NACM) and ASTM A413/A413M. Grade 30. Contact our office to
 determine availability of chain meeting Federal Specification RR-C-271