


1st Chain Supply

12628 E Highway 86
 Neosho, MO 64850
 Sales 1-800-523-2367 Ext "3"
 Fax 417-451-5651



Grade 70 Transport Chain Specifications

An improvement over High Test chain, Grade 70 Transport chain meets stringent Department of Transportation (DOT) regulations with a smaller, easier to handle chain. Identified with "L7" or similar grade marking. Supplied in yellow (gold) chromate finish for easy identification and rust prevention. Available in drums, pails and binder assemblies.

NOT FOR OVERHEAD LIFTING.

Trade Size	Working Load Limit (lbs) (4:1)	Material Diameter "T" (inches)	Inside Length "L" (inches)	Inside Width "W" (inches)	Weight per 100 ft (lbs)
1/4 Reg Link	3150	0.274	1.24	0.46	74
1/4 Short Link	3150	0.274	0.84	0.47	76
5/16 Reg Link	4700	0.334	1.12	0.48	97
5/16 Short Link	4700	0.334	0.98	0.46	101
3/8 Reg Link	6600	0.392	1.30	0.60	137
3/8 Short Link	6600	0.392	1.14	0.54	146
7/16 Reg Link	8750	0.458	1.37	0.87	209
1/2 Reg Link	11300	0.51	1.56	0.81	270
5/8 Reg Link	15800	0.612	1.93	0.92	354
All items meet Fed Spec RR-C-271 Type 1, Class 3 (latest revision)			<i>DO NOT USE FOR OVERHEAD LIFTING.</i>		
			<i>Do not exceed working load limit.</i>		

Manufactured to specifications developed by the National Association of Chain Manufacturers (NACM) and ASTM A413/A413M. Grade 70. Contact our office to determine availability of chain meeting Federal Specification RR-C-271